

Wiring, Printed – Flexible Material Constructions – Component

COMPANY

HUADING GROUP CO LTD

12/F, Nanfung Centre

264-298 Castle Peak Rd

Tsuen Wan, Hong Kong

E484912

Type	Cond Width		Cond Thk	SS/DS/	Max Area Diam	Report date After	Surface Mount Technology	Assembly Solder Process	Solder Temp °C	Solder Limits °C	Solder sec	Max Oper Temp °C	Flame Class	Meets UL796F	C T
	Min	Edge													
	mm	mm													
2022-01-01															
Multilayer flexible materials interconnect constructions, Flammability Recognition only															
HD-FM03	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-FM04	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-FM05	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
Multilayer flexible materials interconnect constructions, Flexible application															
HD-FM06	0.06	0.06	14 Int:35	DS	25.4	No	-	-	-	288	10	105	V-0	-	-
Multilayer flexible materials interconnect constructions, for rigid-flex application															
HD-FM02	0.07	0.07	12 Int:35	DS	50.8	No	-	-	-	288	10	105	V-0	-	-
Multilayer Rigid Flex Composite, Flexible Materials Interconnect Constructions, for flexible application															
HD-RF06(Note1)	0.06	0.06	12	DS	25.4	No	-	-	-	280	20	105	V-0	-	-
Multilayer Rigid Flexible Materials Interconnect Constructions															
HD-FM01	0.08	0.08	9 Int:17	DS	50.8	No	-	-	-	288	10	105	V-0	-	-
Multilayer rigid-flex flexible materials interconnect constructions, Fle-to-install application															
HD-RF08(ASP 1) (Note 3)	0.058	0.058	12 Int:35	DS	18	Yes	Yes	260	3	-	-	105	V-0	All	4
Multilayer rigid-flex flexible materials interconnect constructions, Flexible application															
HD-RF09(Note 2)	0.05	0.05	12 Int:35	DS	18	Yes	Yes	260	3	-	-	105	V-0	All	4
HD-RF10(Note 1)	0.06	0.06	14 Int:35	DS	25.4	No	-	-	-	288	10	105	V-0	-	-
HD-RF11 The external copper thickness in flex area is 12-35mic,	0.05	0.05	12 Int:35	DS	25.4	No	-	-	-	288	20	105	V-0	-	-

and it's 12-102mic in rigid area with 35mic maximum internal copper thickness.															
HD-RF12 The external copper thickness in flex area is 12-35mic, and it's 12-102mic in rigid area with 35mic maximum internal copper thickness.	0.05	0.05	12 Int:35	▲ DS	25.4	No	-	-	-	288	20	105	V-0	-	-
Single layer Flex-to-Install, Flexible Materials Interconnect Constructions															
HD-F06	0.07	0.15	12	DS	25.4	No	-	-	-	280	10	105	V-0		-
Single layer flexible materials interconnect constructions															
HD-F11	-	-	-	DS	-	No	-	-	-	288	10	-	VTM-0	-	-
HD-F12	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
Single layer flexible materials interconnect constructions, for flexible application															
HD-DF16	0.05	0.05	12	DS	25.4	No	-	-	-	280	20	105	V-0	-	-
Single layer flexible materials interconnect constructions, Flammability Recognition only															
HD-F01	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-F02	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-F03	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-F04	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-F05	-	-	-	DS	-	No	-	-	-	288	10	-	VTM-0	-	-
HD-F07	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-F08	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-F09	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
HD-F10	-	-	-	DS	-	No	-	-	-	288	10	-	V-0	-	-
Single layer flexible materials interconnect constructions, Flexible application															
HD-DF04	0.05	0.05	12	DS	25.4	No	-	-	-	288	20	105	V-0	All	*
HD-DF05	0.05	0.05	12	DS	25.4	No	-	-	-	288	20	105	V-0	-	*
HD-SF03	0.06	0.06	14	SS	25.4	No	-	-	-	288	10	105	V-0	-	*
Single layer flexible materials interconnect constructions, for flexible application															
HD-DF06(ASP 1)	0.058	0.058	12	DS	18	Yes	Yes	260	3	-	-	105	V-0	All	4
HD-SF01	0.05	0.05	12	SS	25.4	No	-	-	-	280	20	105	V-0	-	-

* – CTI marking is optional and may be marked on the printed wiring board.

(ASP 1) – Assembly solder process evaluated to IPC-TM-650, 2.6.27 Thermal Stress Assembly Simulation.

(Note 1) – The external copper thickness in flex area is 14–35mic, and it's 12–102mic in rigid area.

(Note 2) – For single layer flexible construction: the external copper thickness is 12mic–35mic. For rigid/flex construction: the external copper thickness is 12mic–102mic.the internal copper thickness is 35mic.

(Note 3) – For multilayer flex-to-install construction: the external copper thickness is 12mic–35mic,the internal copper thickness is 35mic. For rigid/flex construction: the external copper thickness is 12mic–102mic.the internal copper thickness is 35mic.

Note1 – For single layer flexible area, the external copper thickness is 12mic–35mic. For rigid arear, the external copper thickness is 12mic–102mic



Marking: Company name or trademark , or file number and type designation. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2024-02-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."